

Precision Bench Scales

EK-L Series



EK-15KL

15 kg × 0.1 g

Higher resolution

Larger capacity



EK-30KL

3 kg × 0.1 g / 30 kg × 1 g (smart range)

A choice to be made—depending on your intended use!

See reverse side



A&D ...Clearly a Better Value
A&D Company, Limited
<http://www.aandd.jp>

EK-15KL (15 kg × 0.1 g)

Ideal for use where large capacity and high resolution are simultaneously required (e.g. measurements of precious metal blocks, etc.)

EK-30KL (Smart range: 3 kg × 0.1 g / 30 kg × 1 g)


Especially useful when the gross weight exceeds 15 kg, yet 0.1 g readability is necessary to measure the net weight (e.g. measurements of ingredients added into a heavy container, etc.)*1

*1 The EK-30KL can always restore its precision range (3 kg × 0.1 g) with a press of the Re-Zero key.

Common features

- ✓ Large (300 × 210 mm) weighing pan for efficient measurements of bulky objects or quantities
- ✓ Hygienic and scratch-resistant, stainless steel (SUS430) weighing pan cover
- ✓ Easy-to-read LCD display with clear, white backlight (22 mm character height)
- ✓ Multiple weighing units: g, kg, oz, lb, ozt, in addition to pcs (counting mode) and % (percent mode)*2
- ✓ Comparator, display hold, auto power OFF functions
- ✓ Security ring for wire-locking the scale to prevent theft
- ✓ Data output to a PC, printer, etc., via RS-232C interface
- ✓ Operation with either AC adapter or optional rechargeable battery

*2 tl (HK general/Singapore) can be added upon request.



Specifications


	EK-15KL	EK-30KL	
Weighing capacity	15 kg	3 kg	30 kg
Minimum weighing value	0.1 g	0.1 g	1 g
Repeatability (standard deviation)	0.3 g	0.3 g	1 g
Linearity	±0.6 g	±0.6 g	±1 g
Sensitivity drift	±20 ppm/°C (10 to 30°C/50 to 86°F)		
Counting mode	0.1 g		
Min. unit weight*3	0.1 g		
No. of samples	5, 10, 25, 50 or 100 pieces		
Percent mode	0.1%		
Min. % display	0.1%		
Min. 100% weight	10 g		
Operating temperature	10 to 40°C/50 to 104°F, 85% RH or less (no condensation)		
Battery life (on a full charge)	Approx. 100 hours (at 25°C with backlight off)		
Weighing pan size	300 × 210 mm		
Net weight	Approx. 4.2 kg	Approx. 4.9 kg	
Calibration weight	15 kg	30 kg	
Standard accessories	AC adapter, Instruction manual		

*3 Factory setting

Options

HC-02i Sealed lead acid rechargeable battery (6 V, 4 Ah)

Dimensions (mm/inches)



AND

...Clearly a Better Value

A&D Company, Limited
 3-23-14 Higashi Ikebukuro Toshima Ku, Tokyo 170-0013 JAPAN
 Telephone:[81](3) 5391-6132 Fax:[81](3) 5391-6148
 http://www.aandd.jp

A&D Technology, Inc.
 4622 Runway Blvd. Ann Arbor, MI 48108 U.S.A
 Telephone:[1](734) 973-1111 Fax:[1](734) 973-1103
 http://www.aanddtech.com

A&D Europe GmbH
 Im Leuschnerpark 4, D-64347 Griesheim,
 GERMANY
 Telephone:[49](6155) 605 250 Fax:[49](6155) 605 100

A&D Technology Trading (Shanghai) Co., Ltd.
 21A, Majesty Building, No.138 Pudong Avenue,
 Pudong New Area, Shanghai, 200120, CHINA
 Telephone:[86](21) 3393-2340 Fax:[86](21) 3393-2347

A&D Europe GmbH UK Branch
 Unit 24/26 Blacklands Way Abingdon Business Park,
 Abingdon, Oxon OX14 1DY UNITED KINGDOM
 Telephone:[44](1235) 550420 Fax:[44](1235) 550485

A&D Australasia Pty Ltd.
 32, Dew Street, Thebarton, South Australia 5031 AUSTRALIA
 Telephone:[61](8) 8301-8100 Fax:[61](8) 8352-7409

A&D KOREA Limited
 817, Manhattan Bldg., 33, Gukjegeumyung-ro 6-gil,
 Yeongdeungpo-gu, Seoul, 150-749, KOREA
 Telephone:[82](2) 780-4101 Fax:[82](2) 782-4280